




Y STRAINER

PN 16



DESCRIPTION

FACE TO FACE DIMENSIONS ACCORDING TO
DIN3202 F1

The mesh of wire screen or the hole dimension of the perforated screen can be as per the customer's requirement

FLANGE DIMENSIONS ACCORDING TO
DIN2501 PN10/PN16

NOMINAL PRESSURE
PN10/PN16

MATERIALS

NO.	PART	MATERIAL	MATERIAL
1	BODY	CAST IRON OR DUCTILE IRON	GGG25 OR GGG40
2	PLUG	CAST IRON OR DUCTILE IRON OR STEEL	GGG25 OR GGG40
3	COVER	CAST IRON OR DUCTILE IRON	GGG25 OR GGG40
4	SCREEN	STAINLESS STEEL	304SS
5	GASKET	GRAPHITE OR RUBBER	

DIMENSION (MM)

DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
L	130	150	160	180	200	230	290	310	350	400	480	600	730	850	980	1100
≈H	72	80	90	105	105	170	205	210	235	270	310	390	430	500	670	780
D	95	105	115	140	150	165	185	200	220	250	285	340	405	460	520	580
K	65	75	85	100	110	125	145	160	180	210	240	295	355	410	470	525
D1	47	58	68	78	88	102	122	138	158	188	212	268	320	378	438	490

* Flange dimensions can be as per Bs10 Table D/E, JIS10K, etc...